

STF SERIES NEW CONSTRUCTION REPAIR FITTING







The STF Fittings are available for new construction or to replace damaged or deteriorated rubber test fittings.

secondary ther options ed after LATION be used ng in both repair

Pipe	Part No.	ID	OD
3" x 2" RTIIA	PF-STF-1C-32	2.4"	3.6"
4" x 3" RTIIA	PF-STF-1C-43	3.6"	4.6"
6" x 4" RTIIA	PF-STF-1C-64	4.6"	6.6"
2" LCX	PF-STF-1C-L2	2.4"	2.7"
3" LCX	PF-STF-1C-L3	3.6"	3.9"



PF-STF-1C-32



PART NUMBER LEGEND Series Generation PF: Penetration 1: 1st Gen. Fitting Pipe 32: 3"x2" RTIIA 43: 4"x3" RTIIA 64: 6"x4" RTIIA L2: 2" LCX Model Install STF: STF L3: 3" LCX C: Concentric



MANY PIPE SIZES

Available for size over size and LCX piping.

LEAVE IN PLACE

STF Fittings leave the secondary piping open, unlike other options which must be removed after testing.

VERSATILE INSTALLATION

STF Series fittings can be used to test secondary piping in both new construction and repair applications.

COST EFFECTIVE

PCI's penetration fittings are the most affordable fiberglass fittings on the market, with a similar cost to rubber or plastic fittings.

PERMANENT BONDING

EP2A is used to bond fittings to fiberglass and steel. It has great gap filling properties and excellent sag resistance, making it a simple and dependable bonding solution.

LONG-TERM SOLUTION

100% fiberglass construction provides superior strength and ensures the fitting will withstand long-term exposure to all fuels, including ethanol. These can replace rubber or plastic boots.



