



## TPT SERIES NEW CONSTRUCTION FITTING



The Testable Primary Termination New Construction Fitting brings both convenience and innovation for a simple and permanent installation.

### INTEGRATED TEST PORT

The integrated test port eliminates the need for a separate test boot.

### MISALIGNMENT FLEXIBILITY

Works with angled pipe entries up to 10° and allows for ±1" pipe misalignment.

### COST EFFECTIVE

PCI's penetration fittings are the most affordable fiberglass fittings on the market, with a similar cost to rubber or plastic fittings.

### PERMANENT BONDING

EP2A is used to bond fittings to fiberglass and steel. It has great gap filling properties and excellent sag resistance, making it a simple and dependable bonding solution.

### LONG-TERM SOLUTION



100% fiberglass construction provides superior strength and ensures the fitting will withstand long-term exposure to all fuels, including ethanol. These can replace rubber or plastic boots.



PF-TPT-2F-32

| Part No.      | Install   | Pipe          | Length | ID   | OD    |
|---------------|-----------|---------------|--------|------|-------|
| PF-TPT-2F-32  | Flat Wall | 3" x 2" RTIIA | 6"     | 2.4" | 7"    |
| PF-TPT-2F-43  | Flat Wall | 4" x 3" RTIIA | 6"     | 3.8" | 7.8"  |
| PF-TPT-2F-64  | Flat Wall | 6" x 4" RTIIA | 8.5"   | 4.8" | 10"   |
| PF-TPT-2F-L2* | Flat Wall | 2" LCX        | 6"     | 2.4" | 7"    |
| PF-TPT-2F-L3* | Flat Wall | 3" LCX        | 6"     | 3.8" | 7.8"  |
| PF-TPT-2F-L4* | Flat Wall | 4" LCX        | 8.5"   | 4.8" | 10.8" |

\*LCX Adapter Included



### PART NUMBER LEGEND

#### Series

PF: Penetration Fitting

#### Generation

2: 2nd Gen.

#### Pipe

32: 3" x 2" RTIIA  
43: 4" x 3" RTIIA  
64: 6" x 4" RTIIA  
L2: 2" LCX  
L3: 3" LCX  
L4: 4" LCX

PF

TPT

2

F

32

Model  
TPT: TPT

Install  
F: Flat Wall

